



RM. 517, NEW CITY CENTRE, 2 LEI YUE MUN ROAD KWUN TONG, KOWLOON. HK TEL: 0086-393-4662488

www.united-beads.com

## TECHNICAL DATA SHEET

#### **GLASS BEAD FOR ROAD MARKING GB 850-150**

# **DESCRIPTION**

#### **Glass Bead for Road Marking:**

Improve the road marking line contrary reflection function. When driving at night, the lamp shines on the marking line with glass bead in it, the ray of lamp is reflected back parallely. So the driver can look at the road clearly and drive safely at night.

### TYPICAL SPECIFICATION

Item	Glass bead size(μm)	Glass bead percentage(%)
GB 850-150	>850	0-5
	850-600	5-20
	600-300	30-75
	300-180	10-30
	<180	0-15

Choices of different size glass bead between 0µm-1180µm according to different functions.

Products can meet international standard including English BS6088, AASHTO M247-81 (1996), EN1423/EN1424 standard etc.

## **TECHNICAL REQUESTS**

Appearance: Colorless and transparent ball, no visible bubbles and impurity.

Spherical beads:  $\geq$ **90%** (600< Sieve size < 850um, spherical beads  $\geq$ 80%).

Density: 2.4-2.6g/cm3.

Refractive index: Nd ≥1.50

Glass bead composition: The glass bead is made of sodium and calcium. SiO2 >68%

### **PACKAGING**

Using double-deck package, the inner is polythene film and its thickness is not less than 0.5mm, the outer is plastic woven bag to prevent leak or damp. The net weight of each bag is  $25\pm0.2$ kg,  $1000\pm8$ kg, or according to clients' requirement.

The information in this bulletin is believed to be accurate, but all recommendations are made without warranty since the conditions of use are beyond UNITED BOLTEN BEADS' control. The listed -properties are illustrative only, and not product specifications. UNITED BOLTEN BEADS disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of its products in combination with other material or in any process.